Ordering Guide for UltraUMA™
Model UMA
(1/2" LO, 3/4" LO, 1" XLO)

Part # Template w/Sample Part #:

U	M	A	–	0	5	0	L	F	0	5	0	S	0	3	0	A		X	H	C		B	N	A

MODEL
UMA

VALVE TRIM
– = Brass
+ = SS

SIZE CODE	
050L	= 1/2" LO
075L	= 3/4" LO
100X	= 1" XLO

FIXED END
F = Female
S = Sweat
P = NexPress
L = NexLok

UNION END TYPE *
F = Female
M = Male
S = Sweat
P = NexPress
L = NexLok

UNION END SIZE*	
038	= 3/8"
050	= 1/2"
075	= 3/4"
100	= 1"

** Please consult individual component spec sheets and/or the **Union End Connection Size Guide** to determine if desired size and type is available.*

ACTUATOR OPTIONS
3 Digit Code for Actuator *
or
BNA = Bracket No Actuator
Blank = Valve only
* See TCV Catalog for Actuator Ordering Codes

OPTION ORDER CODE(S)
X = Extension Kit (w/PTEs)
or
@ = Extension Kit (w/PTEBs) *incl. Extended Actuator Shaft*
H = Hanging Tag Option (HT)
C = Check Valve (CV)

PT CAP OPTION
– = Composite
% = Brass

"Cv" SELECTIONS
A=0.5 B=0.8 C=1.7 D=2.2 E=3.5 F=4.3 G=6.1 H=9.1

FLOW RATE (GPM)	
UMA	Available Flow Rates (gpm)
050L, 075L 100X	0.33, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.25, 2.5, 2.75, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0
Please note the implied decimal point in flow rate entry. *Example: Enter 01.5 gpm as "015", 12.0 gpm as "120", etc.*	

Copyright ©2012 Nexus Valve, Inc. All Rights Reserved
(Rev: 09/20/16)