



Ordering Guide for UltraMatic™ Model UMF Automatic Flow Control (1/2", 3/4" & 1" FNPT)

Part # Template w/Sample Part #:

U M F - 0 5 0 F - 0 5 0 - P P - X H

MODEL
UMF

SIZE & CONNECTION
050F = 1/2" FNPT
075F = 3/4" FNPT
100F = 1" FNPT

OPTION ORDER CODE(S)
Extend Accessories (as applicable)
X = Ext. Accessories (w/PTE, MV-025L)
or
@ = Ext. Accessories (w/PTEB, MV-025L)
H = Hanging Tag Option (HT)

PT & BD CAP OPT
- = Composite
% = Brass

PORT ACCESSORIES
Available Accessories for NPT Ports
PP = PT Test Plugs (Hi/Lo)
GG = Plugs (PG-9/16 x 2)

FLOW RATE (GPM)	
SIZE	Available Flow Rates (gpm)
050F	0.33, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.25 2.5, 2.75, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0
075F	0.33, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.25, 2.5, 2.75, 3.0, 3.5 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0, 9.0, 10.5, 11.0, 12.0, 13.0, 14.0, 15.0
100F	0.33, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.25, 2.5, 2.75, 3.0, 3.5 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0, 9.0, 10.5, 11.0, 12.0, 13.0, 14.0, 15.0
<i>Please note the implied decimal point in flow rate entry. Example: Enter 01.5 gpm as "015", 12.0 gpm as "120", etc.</i>	