



# NEXUS

# UltraMatic™ Model UMNL

## Submittal Schedule

(1/2", 3/4", 1")

SIZE [inches]	Valve Body Size	PSID (range)	GPM (± 5.0%)
1/2	1	2 - 45	0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0
3/4	2	2 - 45	0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 7.0
1	2	2 - 45	0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 7.0

H .... HT. HANGING TAG with Model No., Location, Flow Rate ( <i>Maximum 7 Characters</i> )
X .... PTE. PRES / TEMP TEST PLUG EXTENSION; 1/16" O.A.L.

Item	Qty.	Cv	Model Designation	Tagging Information <small>(Maximum 7 Characters)</small>

**ORDER DATA**

Sample Part #:  

U	M	N	L	1	-	0	5	0	F	-	0	5	0	F	-	0	5	0	-	X	H
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Model \_\_\_\_\_

Size & Type - 1st FE \_\_\_\_\_

Size & Type - 2nd FE \_\_\_\_\_

Flow Rate (GPM) \_\_\_\_\_

Option Order Codes \_\_\_\_\_

*Please consult the Ordering Guide in the Nexus Valve catalog for complete part number and ordering information.*

PROJECT \_\_\_\_\_

CONTRACTOR \_\_\_\_\_

PO/JOB NO. \_\_\_\_\_

ENGINEER \_\_\_\_\_

REPRESENTATIVE \_\_\_\_\_

DATE \_\_\_\_\_



UltraMatic™ Model UMNL is tested and certified to NSF/ANSI/CAN 61 & NSF/ANSI 372 for Lead Free compliance.

9982 E. 121st Street, Fishers, IN 46037  
 Copyright © 2019 Nexus Valve, Inc. All Rights Reserved