


NEXUS Nexus Venturi TM Model NVGB Grooved End Venturi Flore 12

(2½" thru 12")



DIMENSIONS [inches]										
SIZE	I A	Ag	В	R	С	Cv	WT. [lbs]			
[inches]	, ,			(Flange)			NVF	BV	FGA ¹	
21/2	5.65	11.96	3.75	3.50	8.3	43	18.0	11.5	17.8	
3	8.13	14.73	4.00	3.75	8.4	84	24.5	12.0	20.2	
4	11.00	18.36	4.45	4.50	9.2	149	36.5	18.6	33.8	
5	11.53	19.40	5.00	5.00	9.5	220	45.0	22.5	44.3	
6	12.15	19.90	5.51	5.50	10.2/11.6 ²	402	57.0	24.5/38.0 ²	52.0	
8	12.90	21.50	6.55	6.75	13.2	677	84.5	49.5	76.3	
10	13.90	23.13	7.60	8.00	14.5	995	119.5	72.0	120.1	
12	15.65	25.46	8.60	9.50	16.3	1749	181.5	95.0	163.0	
NOTES: 1 Weight of 2 Grooved Adapters with hardware; 2 Model BV-0600/BV-0600GB										

FLOW RATE RECOMMENDATION GUIDE						
SIZE	IDEAL FLOW RANGES [GPM]					
[inches]	Min. Flow (@ 10 Inch WC)	Max. Flow (@ 100 Inch WC)				
21/2	26.0	82.0				
3	50.0	158.0				
4	89.0	281.0				
5	131.0	415.0				
6	240.0	758.0				
8	404.0	1,277.0				
10	594.0	1,877.0				
12	1,044.0	3,300.0				

BASIC INSTALLATION NOTES

- -MUST BE INSTALLED IN THE INDICATED FLOW DIRECTION
- -CAN BE ROTATED 360° AROUND PIPE AXIS FOR INSTALLATION
- -NO STRAIGHT PIPE DIAMETERS ARE REQUIRED
- -ALLOW A MINIMUM OF 10 STRAIGHT PIPE DIAMETERS AFTER A PUMP DISCHARGE
- -150# CLASS B FLANGES ALSO MATE TO 125# FLANGES
- -NVGB SHIPS WITH BUTTERFLY VALVE INSTALLED HAND TIGHT

ORDER DATA N V G B - 0 4 0 0 -Model Size Option Order Code (PTE) Option Order code (HT) Option Order code (GB)

MATERIALS & DESIGN DATA

VENTURI BODY (PIPE)P235GH - PRESSURE VESSEL STEEL,

(EQUIVALENT TO ST 35), 230 PSI, -4°F to 250°F

STANDARD 150# CLASS B FLANGES (MATES TO 125# FLANGES ALSO)

VENTURI INSERTP235T1 - CARBON STEEL

(EQUIVALENT TO ST 37)

FLANGESS235JR - CARBON STEEL, ASME B16.5,

STANDARD 150# CLASS B

.....EPOXY COATED CAST IRON, ASTM A126, **BUTTERFLY VALVE**

CLASS B, LUG TYPE BUTTERFLY VALVE, 225 PSIG, 250°F, 304 STAINLESS STEEL DISK,

416 STAINLESS STEEL SHAFT, ON-OFF w/ HANDLE

BOLTSZINC PLATED STEEL

GROOVED ADAPTERSDUCTILE IRON. ASTM A 395, 175 PSIG, 250°F.

STANDARD 125# CLASS B FLANGES

ACCURACY±3%

Α	C	C	Ε	S	S	0	R	l	Ε	S
									_	

r1680	Order <u>Part No. Description</u>	
	GB BV-0600GB. GEARBOX WITH H	AND WHEEL
Ultraster	H HT. HANGING TAG with Model No., Location (Maximum 7 Ch.	paracters)
Ħ	X PTE PRES / TEMP TEST PLUG	EXTENSION

1%₆" O.A.L.

PROJECT	
CONTRACTOR	
PO/JOB NO	
ENGINEER	
REPRESENTATIVE	
DATE	