



DIMENSIONS [inches]					
SIZE [inches]	A	B	WT ² [lbs]	FILTER AREA [sq. in.]	Cv ¹
½	2.80	1.80	0.32	2.70	5.5
¾	3.82	2.50	0.70	7.40	9.0
1	4.92	3.75	1.43	16.70	13.0

¹Cv based on new clean filter element; ²Filter and Cap included

ACCESSORIES

	<input type="checkbox"/>	B	... BD-025. BLOWDOWN / VENT / DRAIN ¼" MNPT (for YSS-050S & YSS-075S)
			... BD-050. BLOWDOWN / VENT / DRAIN ½" MNPT (for YSS-100S) 325°F, 600 PSIG, ¾" hose bib & cap
	<input type="checkbox"/>	G	... PG-025. PLUG ¼" MNPT (for YSS-050S & YSS-075S)
			... PG-050. PLUG ½" MNPT (for YSS-100S)

MATERIALS & DESIGN DATA

BODYDZR BRASS (desincification resistant),
600 WOG, 325°F

STRAINER CAPDZR BRASS (desincification resistant),
600 WOG, 325°F
¼" or ½" FNPT PORT

CAP SEALFKM O-RING

FILTER SCREEN304 STAINLESS STEEL, REMOVABLE,
20 MESH / 40 MESH (optional)

ORDER DATA

Sample Part #:
Y S S - 0 5 0 S - B

Model _____
YSS - Strainer

Size _____
½" S = 050S; ¾" S = 075S; 1" = 100S
S for Sweat

Option Order Codes (Accessories) _____

PROJECT _____

CONTRACTOR _____

PO/JOB NO. _____

ENGINEER _____

REPRESENTATIVE _____

DATE _____