



Nextrol™/TwinTube™ Pitot

Submittal Schedule

(2½" thru 12")

SIZE (Inches)	FLOW COEFFICIENTS (Cv)
2½	119
3	181
4	326
5	505
6	732
8	1273
10	2005
12	2800

- ### ACCESSORIES
- A AV-025. AUTOMATIC AIR VENT; 250°F, 150 PSIG, positive shut-off, ¼" MNPT
 - B BD-050. BLOWDOWN / VENT / DRAIN; 325°F, 600 PSIG, ¾" hose bib & cap; ½" MNPT
 - GB BV-0600GB. GEARBOX WITH HAND WHEEL (for 6" Nextrol only)
 - O SV-025. SHUT-OFF VALVE; 300°F, 600 PSIG, ¼" MNPT x ¼" FNPT
 - V MV-025. MANUAL AIR VENT; 325°F, 400 PSIG, Side Discharge, ¼" MNPT
 - W TW-075. THERMOMETER WELL; brass, 1½" well, 3½" O.A.L., ¼" MNPT
 - X MV-025L. MANUAL AIR VENT EXTENDED; 325°F, 400 PSIG, Side Discharge, 2¼" O.A.L., ¼" MNPT

Item	Qty.	GPM	Model Designation	Tagging Information <small>(Maximum 7 Characters)</small>

ORDER DATA

Sample Part #:

N	X	G	B	0	4	0	0	-	V	G	B	P	-				
---	---	---	---	---	---	---	---	---	---	---	---	---	---	--	--	--	--

Model _____
Nextrol Size _____
Port Accessories _____
Option Order Codes _____
Gearbox Option (for 6" Nextrol only) _____

Please consult the Ordering Guide in the Nexus Valve catalog for complete part number and ordering information.

PROJECT _____
CONTRACTOR _____
PO/JOB NO. _____
ENGINEER _____
REPRESENTATIVE _____
DATE _____