



MATERIALS & DESIGN DATA

BODIES, END PIECESHOT FORGED BRASS ASTM B283 FNPT, SWT, NexPress, NexLok 600 WOG, 325°F (NexPress: 200 PSIG, 250°F / NexLok: 250 PSIG, 200°F), INTERCHANGEABLE UNION ENDS
HANDLES & NUTSZINC PLATED / PVC COATED
BALLSHARD CHROME PLATED BRASS / STAINLESS STEEL (optional)
BALL SEALSTEFLON
SHAFTSBRASS / STAINLESS STEEL (optional) BLOWOUT-PROOF SHAFT
SHAFT SEALSDUAL FKM O-RINGS
UNION SEALSFKM O-RING
CAP SEAL (UM)FKM O-RING
FLOW CARTRIDGE304 STAINLESS STEEL MOVING PARTS IN BRASS HOUSING, PAT # 8517051
CARTRIDGE SEALEPDM
HOSE SPECS400 PSI (½" thru 1"), 248°F 300 PSI (1¼" thru 1½"), 248°F
HOSE COREREINFORCED EPDM
HOSE BRAIDSTAINLESS STEEL
HOSE FITTINGSBRASS OT58
HOSE GASKETEPDM

FLOW RATE SELECTIONS

SIZE [inches]	PSID (range)	GPM (± 5.0%)
½ LO, ¾ LO, 1 XLO	2 - 45	0.33, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.25, 2.5, 2.75, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0
	4 - 55	7.0, 8.0
½ STD, ¾ STD, 1 LO, 1¼ LO	2 - 45	0.33, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.25, 2.5, 2.75, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0, 9.0, 10.5
	5 - 65	11.0, 12.0, 13.0, 14.0, 15.0
1 STD, 1¼ STD, 1½ LO	2 - 45	7.0, 8.0, 9.0, 10.0, 11.0, 12.0, 13.0, 14.0, 15.0 16.0, 17.0, 18.0, 19.0, 20.0, 21.0, 22.0
	2 - 60	24.0, 25.0, 30.0, 35.0
	4 - 70	40.0, 45.0

ACCESSORIES

	Order Code	Part No.	Description
	<input type="checkbox"/> C CV-1, CV-2.	CHECK VALVE CV-1 for ½"LO, ¾"LO, 1"XLO; CV-2 for ½"STD, ¾"STD, 1"LO, 1¼"LO; Center Guided, Non-Slam Check
	<input type="checkbox"/> H HT.	HANGING TAG with Model No., Location, Flow Rate (Maximum 7 Characters)
	<input type="checkbox"/> K ES.	EXTENSION KITS
	<input type="checkbox"/> L SL.	SHORT LEVER HANDLE
	<input type="checkbox"/> M HNA.	HOSE ADAPTER. Straight pipe threads and MNPT pipe threads
	<input type="checkbox"/> S HSA.	HOSE ADAPTER. Straight pipe threads and Sweat end
	<input type="checkbox"/> P HPA.	HOSE ADAPTER. Straight pipe threads and NexPress end
	<input type="checkbox"/> T T.C.V.	Handling (TC) & Hard Piped (CC) (See TCV Catalog for Order Codes)

ORDER DATA

Sample Part #: **A2N-150LSM1C0150M0**

Model	A	2	N	-	1	5	0	L	S	M	1	C	0	1	5	0	M	0
Valve Trim																		
Coil Pak Size																		
Branch Line																		
Connection to TCV																		
Connection to Coil																		
Flow Rate (GPM)																		
Hose Adapters (Con. Type & Red. Code)																		
Accessory Cap Option																		
Option Order Codes (Accessories)																		

PROJECT _____

CONTRACTOR _____

PO/JOB NO. _____

ENGINEER _____

REPRESENTATIVE _____

DATE _____

Please consult the "Ordering Guide" section in Nexus Valve Catalog for complete part number and ordering information.