



MATERIALS & DESIGN DATA

- BODIES, END PIECESHOT FORGED BRASS ASTM B283
(CAST BRASS: UM (1½"STD, 2", 2½"))
FNPT, SWT, NexPress, NexLok
600 WOG, 325°F (NexPress: 200 PSIG, 250°F /
NexLok: 250 PSIG, 200°F),
INTERCHANGEABLE UNION ENDS
- HANDLES & NUTSZINC PLATED / PVC COATED
- BALLSHARD CHROME PLATED BRASS /
STAINLESS STEEL (optional)
- BALL SEALSTEFLON
- SHAFTSBRASS / STAINLESS STEEL (optional)
BLOWOUT-PROOF SHAFT
- SHAFT SEALSDUAL FKM O-RINGS
- UNION SEALSFKM O-RING
- CAP SEAL (UM)FKM O-RING
- FLOW CARTRIDGE304 STAINLESS STEEL MOVING PARTS
IN BRASS HOUSING, PAT # 8517051
- CARTRIDGE SEALEPDM

FLOW RATE SELECTIONS

SIZE [inches]	PSID (range)	GPM (± 5.0%)
½ LO, ¾ LO, 1 XLO	2 - 45	0.33, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.25, 2.5, 2.75, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0
	4 - 55	7.0, 8.0
½ STD, ¾ STD, 1 LO, 1¼ LO	2 - 45	0.33, 0.5, 0.75, 1.0, 1.25, 1.5, 1.75, 2.0, 2.25, 2.5, 2.75, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0, 9.0, 10.5
	5 - 65	11.0, 12.0, 13.0, 14.0, 15.0
1 STD, 1¼ STD, 1½ LO	2 - 45	7.0, 8.0, 9.0, 10.0, 11.0, 12.0, 13.0, 14.0, 15.0 16.0, 17.0, 18.0, 19.0, 20.0, 21.0, 22.0
	2 - 60	24.0, 25.0, 30.0, 35.0
1½ STD, 2, 2½	4 - 70	40.0, 45.0
	2 - 45	25.0, 30.0, 35.0, 40.0, 45.0, 50.0, 55.0, 60.0, 65.0, 70.0, 75.0
	5 - 50	80.0, 85.0, 90.0, 95.0, 100.0

ACCESSORIES

- | | Order Code | Part No. | Description |
|--|--------------------------|----------|---|
| | <input type="checkbox"/> | C | CV-1, CV-2. CHECK VALVE
CV-1 for ½"LO, ¾"LO, 1"XLO;
CV-2 for ½"STD, ¾"STD, 1"LO, 1¼"LO;
Center Guided, Non-Slam Check |
| | <input type="checkbox"/> | H | HT. HANGING TAG
with Model No., Location, Flow Rate
(Maximum 7 Characters) |
| | <input type="checkbox"/> | K | ES. EXTENSION KITS |
| | <input type="checkbox"/> | L | SL. SHORT LEVER HANDLE |
| | <input type="checkbox"/> | T | T.C.V. Handling (TC) & Hard Piped (CC)
(See TCV Catalog for Order Codes) |
| | <input type="checkbox"/> | V | MV-025. MANUAL AIR VENT
325°F, 400 PSIG, ½" MNPT, Side Discharge |

ORDER DATA

Sample Part #:

AX - 150LSM1S0150 - N

- Model
- Valve Trim
- Coil Pak Size
- Branch Line
- Connection to TCV
- Connection to Coil
- Flow Rate (GPM)
- Accessory Cap Option
- Optional (UM) 3rd Port & Accessory (N=NO 3rd Port)
- Option Order Codes (Accessories)

Please consult the "Ordering Guide" section in Nexus Valve Catalog for complete part number and ordering information.

PROJECT _____

CONTRACTOR _____

PO/JOB NO. _____

ENGINEER _____

REPRESENTATIVE _____

DATE _____