



MATERIALS & DESIGN DATA	
BODIES, END PIECESHOT FORGED BRASS ASTM B283 FNPT, SWT, NexPress, NexLok 600 WOG, 325°F (NexPress: 200 PSIG, 250°F / NexLok: 250 PSIG, 200°F), INTERCHANGEABLE UNION ENDS
HANDLE & NUT (UX)ZINC PLATED / PVC COATED
BALLSHARD CHROME PLATED BRASS / STAINLESS STEEL (optional)
BALL SEALSTEFLON
SHAFTSBRASS / STAINLESS STEEL (optional) BLOWOUT-PROOF SHAFT
SHAFT SEALSDUAL FKM O-RINGS
UNION SEALSFKM O-RING
MB BALANCING GLOBEBRASS
MB HANDLEABS
MB EXTENSIONBRASS, ABS
HOSE SPECS400 PSI (1/2" thru 1"), 248°F
HOSE COREREINFORCED EPDM
HOSE BRAIDSTAINLESS STEEL
HOSE FITTINGSBRASS OT58
HOSE GASKETEPDM

FLOW RATE RECOMMENDATION GUIDE		
SIZE [Inches]	IDEAL FLOW RANGES [gpm]	
	Min.	Max.
1/2, 3/4 LO, 1 LO	0.25	8.00

ACCESSORIES		
Order Code	Part No.	Description
<input type="checkbox"/> C	CV-1	CHECK VALVE Center Guided, Non-Slam Check
<input type="checkbox"/> H	HT	HANGING TAG with Model No., Location, Flow Rate (Maximum 7 Characters)
<input type="checkbox"/> K	PTE, ES-1, ES-MB, UNSX-YA1, UAPX-YA1	PRES / TEMP TEST PLUG EXTENSION 1 1/8" O.A.L. EXTENDED HANDLE Stationary housing for full-height vapor barrier EXTENSION; 3" O.A.L. ACTUATOR SHAFT EXTENDED
<input type="checkbox"/> M	HNA	HOSE ADAPTER. Straight pipe threads and MNPT pipe threads
<input type="checkbox"/> S	HSA	HOSE ADAPTER. Straight pipe threads and Sweat end
<input type="checkbox"/> P	HPA	HOSE ADAPTER. Straight pipe threads and NexPress end

ORDER DATA	
Sample Part #:	
Model	M X A - 0 7 5 L F C O M 0
Valve Trim	
Coil Pak Size	
Branch Line	
Connection to Coil	
Hose Adapters (Con. Type & Red. Code)	
Accessory Cap Option	
Option Order Codes (Accessories)	
Actuator Option (3-digit code for Actuator, BNA=bracket only, blank=valve only)	

PROJECT _____

CONTRACTOR _____

PO/JOB NO. _____

ENGINEER _____

REPRESENTATIVE _____

DATE _____

Please consult the "Ordering Guide" section in Nexus Valve Catalog for complete part number and ordering information.