



## MATERIALS & DESIGN DATA

BODIES, END PIECES	.....HOT FORGED BRASS ASTM B283 FNPT, SWT, NexPress, NexLok 600 WOG, 325°F (NexPress: 200 PSIG, 250°F / NexLok: 250 PSIG, 200°F), INTERCHANGEABLE UNION ENDS
HANDLES & NUTS	.....ZINC PLATED / PVC COATED
BALLS	.....HARD CHROME PLATED BRASS / STAINLESS STEEL (optional)
BALL SEALS	.....TEFLON
SHAFTS	.....BRASS / STAINLESS STEEL (optional) BLOWOUT-PROOF SHAFT
SHAFT SEALS	.....DUAL FKM O-RINGS
UNION SEALS	.....FKM O-RING
HOSE SPECS	.....400 PSI (½" thru 1"), 248°F 300 PSI (1¼" thru 1½"), 248°F
HOSE CORE	.....REINFORCED EPDM
HOSE BRAID	.....STAINLESS STEEL
HOSE FITTINGS	.....BRASS OT58
HOSE GASKET	.....EPDM

## ACCESSORIES

	Order Code	Part No.	Description
	<input type="checkbox"/> C	CV-1, CV-2	CHECK VALVE CV-1 for ½", ¾" LO & 1" LO CV-2 for ¾" STD, 1" STD & 1¼" LO; Center Guided, Non-Slam Check
	<input type="checkbox"/> H	HT	HANGING TAG with Model No., Location, Flow Rate (Maximum 7 Characters)
	<input type="checkbox"/> K	ES	EXTENSION KITS
	<input type="checkbox"/> L	SL	SHORT LEVER HANDLE
	<input type="checkbox"/> M	MS-1	MEMORY STOP 304 stainless steel
	<input type="checkbox"/> M	HNA	HOSE ADAPTER. Straight and MNPT pipe threads
	<input type="checkbox"/> S	HSA	HOSE ADAPTER. Straight pipe threads and Sweat end
	<input type="checkbox"/> P	HPA	HOSE ADAPTER. Straight pipe threads and NexPress end
	<input type="checkbox"/> T	T.C.V.	Handling (TC) & Hard Piped (CC) (See TCV Catalog for Order Codes)

## ORDER DATA

Sample Part #:

**N 3 X - 1 0 0 L S M 1 C 0 M 0**

Model	_____
Valve Trim	_____
Coil Pak Size	_____
Branch Line	_____
Connection to TCV	_____
Connection to Coil	_____
Hose Adapters (Con. Type & Red. Code)	_____
Accessory Cap Option	_____
Option Order Codes (Accessories)	_____

Please consult the "Ordering Guide" section in Nexus Valve Catalog for complete part number and ordering information.

PROJECT \_\_\_\_\_

CONTRACTOR \_\_\_\_\_

PO/JOB NO. \_\_\_\_\_

ENGINEER \_\_\_\_\_

REPRESENTATIVE \_\_\_\_\_

DATE \_\_\_\_\_