



MATERIALS & DESIGN DATA

BODIES, END PIECESHOT FORGED BRASS ASTM B283 FNPT, SWT, NexPress, NexLok 600 WOG, 325°F (NexPress: 200 PSIG, 250°F / NexLok: 250 PSIG, 200°F), INTERCHANGEABLE UNION ENDS
HANDLES & NUTSZINC PLATED / PVC COATED
BALLSHARD CHROME PLATED BRASS / STAINLESS STEEL (optional)
BALL SEALSTEFLON
SHAFTSBRASS / STAINLESS STEEL (optional) BLOWOUT-PROOF SHAFT
SHAFT SEALSDUAL FKM O-RINGS
UNION SEALSFKM O-RING
HOSE SPECS400 PSI (½" thru 1"), 248°F 300 PSI (1¼" thru 1½"), 248°F
HOSE COREREINFORCED EPDM
HOSE BRAIDSTAINLESS STEEL
HOSE FITTINGSBRASS OT58
HOSE GASKETEPDM

FLOW RANGE SELECTOR

SIZE [inches]	SELECTOR
½, ¾ LO, 1 LO	1A, 1B, 1C, 1D
¾ STD, 1 STD, 1¼ LO	2A, 2B, 3A, 3B, 3C
1¼ STD, 1½	4A, 5A

ACCESSORIES

	Order Code	Part No.	Description
	<input type="checkbox"/>	H HT. HANGING TAG with Model No., Location, Flow Rate (Maximum 7 Characters)
	<input type="checkbox"/>	K ES. EXTENSION KITS
	<input type="checkbox"/>	L SL. SHORT LEVER HANDLE
	<input type="checkbox"/>	M HNA. HOSE ADAPTER. Straight and MNPT pipe threads
	<input type="checkbox"/>	S HSA. HOSE ADAPTER. Straight pipe threads and Sweat end
	<input type="checkbox"/>	P HPA. HOSE ADAPTER. Straight pipe threads and NexPress end
	<input type="checkbox"/>	T T.C.V. Handling (TC) & Hard Piped (CC) (See TCV Catalog for Order Codes)

ORDER DATA

Sample Part #:

O 3 N - 1 5 0 - S M 1 C 0 5 A M 0

Model	O	3	N	-	1	5	0	-	S	M	1	C	0	5	A	M	0
Valve Trim																	
Coil Pak Size																	
Branch Line																	
Connection to TCV																	
Connection to Coil																	
Flow Range Selector																	
Hose Adapters (Con. Type & Red. Code)																	
Accessory Cap Option																	
Option Order Codes (Accessories)																	

Please consult the "Ordering Guide" section in Nexus Valve Catalog for complete part number and ordering information.

PROJECT _____

CONTRACTOR _____

PO/JOB NO. _____

ENGINEER _____

REPRESENTATIVE _____

DATE _____