



MATERIALS & DESIGN DATA

BODIES, END PIECESHOT FORGED BRASS ASTM B283
FNPT, SWT, NexPress, NexLok
600 WOG, 325°F (NexPress: 200 PSIG, 250°F /
NexLok: 250 PSIG, 200°F),
INTERCHANGEABLE UNION ENDS

HANDLES & NUTSZINC PLATED / PVC COATED

BALLSHARD CHROME PLATED BRASS /
STAINLESS STEEL (optional)

BALL SEALSTEFLON

SHAFTSBRASS / STAINLESS STEEL (optional)
BLOWOUT-PROOF

SHAFT SEALSDUAL FKM O-RINGS

UNION SEALSFKM O-RING

FLOW RANGE SELECTOR

SIZE [inches]	SELECTOR
½, ¾ LO, 1 LO	1A, 1B, 1C, 1D
¾ STD, 1 STD, 1¼ LO	2A, 2B, 3A, 3B, 3C
1¼ STD, 1½	4A, 5A
2, 2½	6A, 6B

ACCESSORIES

Order Code	Part No.	Description
<input type="checkbox"/>	H	HT. HANGING TAG with Model No., Location, Flow Rate (Maximum 7 Characters)
<input type="checkbox"/>	K	ES. EXTENSION KITS
<input type="checkbox"/>	L	SL. SHORT LEVER HANDLE
<input type="checkbox"/>	T	T.C.V. Handling (TC) & Hard Piped (CC) (See TCV Catalog for Order Codes)
<input type="checkbox"/>	V	MV-025. MANUAL AIR VENT 325°F, 400 PSIG, ¼" MNPT, Side Discharge

ORDER DATA

Sample Part #:

OX - 1 2 5 L S M 1 S 0 4 A

Model _____
Valve Trim _____
Coil Pak Size _____
Branch Line _____
Connection to TCV _____
Connection to Coil _____
Flow Range Selector _____
Accessory Cap Option _____
Option Order Codes (Accessories) _____

Please consult the "Ordering Guide" section in Nexus Valve Catalog
for complete part number and ordering information.

PROJECT _____

CONTRACTOR _____

PO/JOB NO. _____

ENGINEER _____

REPRESENTATIVE _____

DATE _____