



MATERIALS & DESIGN DATA

BODIES, END PIECESHOT FORGED BRASS ASTM B283
 CAST BRASS: UY (2", 2½")
 FNPT, SWT, NexPress, NexLok
 600 WOG, 325°F (NexPress: 200 PSIG, 250°F /
 NexLok: 250 PSIG, 200°F),
 INTERCHANGEABLE UNION ENDS

HANDLES & NUTSZINC PLATED / PVC COATED

FILTER SCREEN (UY)304 STAINLESS STEEL,
 20 MESH / 40 MESH (optional)

BALLSHARD CHROME PLATED BRASS /
 STAINLESS STEEL (optional)

BALL SEALSTEFLON

SHAFTSBRASS / STAINLESS STEEL (optional)
 BLOWOUT-PROOF SHAFT

SHAFT SEALSDUAL FKM O-RINGS

UNION SEALSFKM O-RING

CAP SEAL (UY)FKM O-RING

FLOW RANGE SELECTOR

SIZE [inches]	SELECTOR
½, ¾ LO, 1 LO	1A, 1B, 1C, 1D
¾ STD, 1 STD, 1¼ LO	2A, 2B, 3A, 3B, 3C
1¼ STD, 1½	4A, 5A
2, 2½	6A, 6B

ACCESSORIES

Order Code	Part No.	Description
<input type="checkbox"/>	H	HT. HANGING TAG with Model No., Location, Flow Rate (Maximum 7 Characters)
<input type="checkbox"/>	K	ES. EXTENSION KITS
<input type="checkbox"/>	L	SL. SHORT LEVER HANDLE
<input type="checkbox"/>	T	T.C.V. Handling (TC) & Hard Piped (CC) (See TCV Catalog for Order Codes)
<input type="checkbox"/>	V	MV-025. MANUAL AIR VENT 325°F, 400 PSIG, ¼" MNPT, Side Discharge

ORDER DATA

Sample Part #:

OY - 1 2 5 L S M 1 S 0 4 A

Model _____
 Valve Trim _____
 Coil Pak Size _____
 Branch Line _____
 Connection to TCV _____
 Connection to Coil _____
 Flow Range Selector _____
 Accessory Cap Option _____
 Option Order Codes (Accessories) _____

PROJECT _____
 CONTRACTOR _____
 PO/JOB NO. _____
 ENGINEER _____
 REPRESENTATIVE _____
 DATE _____

Please consult the "Ordering Guide" section in Nexus Valve Catalog for complete part number and ordering information.