

Coil Pak™ A2TN

 $(2\frac{1}{2}")$



MATERIALS & DESIGN DATA EPOXY COATED DUCTILE IRON, ASTM A536 **ULTRAMATIC:** 400 PSIG, 350°F FLOW CARTRIDGE: 304 STAINLESS STEEL MOVING PARTS IN BRASS HOUSING, PAT #8517051 CARTRIDGE SEAL: CAST IRON BODY, ASTM A126, CLASS B, **NEXTUBE:** 175 PSIG. 250°F STANDARD 125# CLASS B FLANGES (MATES TO 150# FLANGES ALSO) **BUTTERFLY VALVE:** EPOXY COATED CAST IRON, LUG TYPE BODY, ASTM A126, CLASS B, 225 PSIG, 250°F, EPDM SEAT, 304 STAINLESS STEEL DISK, 416 STAINLESS STEEL SHAFT, ON-OFF w/ HANDLE BOLTS: ZINC PLATED STEEL THREADED ADAPTERS: DUCTILE IRON, ASTM A395, 175 PSIG, 250°F, STANDARD 125# CLASS B FLANGES

FLOW RATES Control Range [PSID]						
SIZE [inches]	LU (2 -4 5)	STD (5-50) for 2½" w/ sm. body STD (2-45) for 2½" w/ lg. body	HI (2-45)	EX HI (4-70)		
		(± 5.0%,	(± 5.0%, 5 GPM increments)			
21/2	25 - 70	75 - 100	105 - 165	140, 160, 180, 200, 220, 240		



ACCESSORIES				
	Order <u>Code</u>	Part No. Description		
	A	AV-025. AUTOMATIC AIR VENT 250°F, 150 PSIG, positive shut-off, X" MNPT		
	В	BD-075. BLOWDOWN / VENT / DRAIN 325°F, 600 PSIG, ¾" hose bib & cap		
United at It.	□ н	HT. HANGING TAG with Model No., Location, Flow Rates (Maximum 7 Characters)		
	v	MV-025. MANUAL AIR VENT 325°F, 400 PSIG, ¼" MNPT, Side Discharge		
	☐ W	TW-075. THERMOMETER WELL ¾" MNPT		
	x	MV-025L. MANUAL AIR VENT EXTENDED 325°F, 400 PSIG, ¾" MNPT, Side Discharge, 2¾" O.A.L PTE. PRES / TEMP TEST PLUG EXTENSION 1¾ ₈ " O.A.L.		

PROJECT
CONTRACTOR
PO/JOB NO.
ENGINEER
REPRESENTATIVE
DATE
Copyright © 2009 Nexus Valve, Inc. All Rights Reserved (Rev: 07/10/15)