





MATERIALS & DESIGN DATA

STRAINEX:	GRAY CAST IRON BODY and END CAP, ASTM A48, CLASS 30, 175 PSIG, 250°F STANDARD 125# CLASS B FLANGES (MATES TO 150# FLANGES ALSO)
SCREEN:	304 S.S., ASTM A167 SIZES OPENINGS 2½" and 3" 0.045 perf 4" thru 12" 0.125 perf
BUTTERFLY VALVE:	EPOXY COATED CAST IRON, LUG TYPE BODY, ASTM A126, CLASS B, 225 PSIG, 250°F, EPDM SEAT, 304 STAINLESS STEEL DISK, 416 STAINLESS STEEL SHAFT, ON-OFF w/ HANDLE
BOLTS:	ZINC PLATED STEEL
GROOVED ADAPTERS:	DUCTILE IRON, ASTM A395, 175 PSIG, 250°F, STANDARD 125# CLASS B FLANGES

ACCESSORIES

	<u>Order Code</u>	<u>Part No.</u>	<u>Description</u>
	<input type="checkbox"/>	GB BV-0600GB.	GEARBOX WITH HAND WHEEL <i>(for 6" thru 12")</i>
	<input type="checkbox"/>	H HT.	HANGING TAG with Model No., Location, Flow Rates <i>(Maximum 7 Characters)</i>
	<input type="checkbox"/>	W TW-075.	THERMOMETER WELL ¾" MNPT
	<input type="checkbox"/>	X PTE.	PRES / TEMP TEST PLUG EXTENSION 1⅞" O.A.L.

ORDER DATA

Sample Part #: **B 2 G Y 0 2 5 0 - - - - - X**

Model	Coil Pak Size	Extended Accessories (ES)	Port Accessories (Return Side)	Port Accessories (Supply Side)	Option Order Codes (HT)	Option Order Codes (GB)
250=2½", 300=3", 400=4", 600=6", 800=8", 1000=10", 1200=12"						

B2GY coil paks include base model Strainex.
 Additional accessories and options may be ordered separately.

PROJECT _____

CONTRACTOR _____

PO/JOB NO. _____

ENGINEER _____

REPRESENTATIVE _____

DATE _____